

MSDS

Material Safety Data Sheet HD

Conforms to ANSI Z-400.1-1993

Chemtel 24 Hour Emergency Response (800) 255-3924

MAINTEX

13300 East Nelson Avenue

City of Industry, CA 91746

(800) 446-1888

1 Chemical Product and Company Identification

Product: Hardwood Floor and Laminate Cleaner **Classification:** Floor Cleaner D00

2 Composition/Information on Hazardous Ingredients

Material	CAS#	%	OSHA(PEL)	TLV(ppm)	Other
Dipropylene Glycol Monomethyl Ether	0345-909-48	<4	N/E	100 ppm	N/A

3 Hazards Identification

Emergency Overview: May cause skin and eye irritation. Avoid skin and eye contact.

CAUTION

Contact with Eyes: May cause moderate irritation, redness, tearing and possible burns, depending on length of contact.

Contact with Skin: Prolonged or repeated contact may cause irritation and drying of skin.

Skin Absorption: No data.

Ingestion Symptoms: Irritation, nausea, vomiting and diarrhea.

Inhalation Symptoms: Excessive exposure to mists/vapors may irritate respiratory tract and result in headache and nausea.

Chronic Effects: No data.

It is important to determine whether exposure is to concentrated or dilute product. The information in this document is intended to deal with exposure to concentrated product. Generally, exposure to diluted product will result in substantially less risk of injury than described herein.

4 First Aid Measures

Eyes: If eyes are contacted, flush with water for 15 minutes. If irritation persists seek medical attention.

Skin: If skin is contacted, wash affected area with soap and water. If irritation persists, seek medical attention.

Inhalation: If discomfort is experienced after prolonged exposure to mists/vapors, remove to fresh air. If breathing is difficult, give oxygen and seek medical attention.

Ingestion: If ingested, do NOT induce vomiting. Give moderate amounts of water to wash out mouth area and dilute remaining residue. Seek medical attention.

10/27/2010

0001

HD

Hardwood Floor and Laminate Cleaner Page 1 of 3

5 Fire Fighting Measures

Flash Point(F° TCC): >200°F

Flammable Limits: LEL No Data

UEL No Data

Auto Ignition Temperature: No Data

Extinguishing Media: Water Spray, Foam, Carbon Dioxide, Dry Chemical

Special Fire Fighting Procedures:

Firefighters should wear a positive pressure NIOSH approved self-contained breathing apparatus.

Unusual Fire and Explosion Hazards:

Containers exposed to heat from fires should be cooled with water fog to prevent container rupture.

6 Accidental Release Measures

Large Spills (55 gallons or more):

Wear rubber boots, gloves and appropriate protective clothing. Shut off source of leak if safe to do so. Dike and contain spill.

Small Spills:

Mop up spill and rinse area.

7 Handling and Storage

Handling: Keep out of reach of children. Follow appropriate hygiene practices.

Storage: Store in a cool, dry place.

8 Exposure Controls/Personal Protection

Ventilation and Engineering Controls:

Local exhaust

Respiratory Protection:

If used according to directions respirator not required.

Protective Gloves:

Rubber Gloves

Eye Protection:

Chemical Splash Goggles

Other Protective Equipment:

